

WISE-2410

LoRaWAN Wireless Condition Monitoring Sensor



FEATURES

- LoRaWAN wireless connectivity
- Built-in 3-axis accelerometer and temperature sensor
- On-board computing. Directly sends VRMS, ARMS, Peak, Displacement, Kurtosis, Crest factor, Skewness and Standard Deviation values to applications
- Support battery power supply, no wiring installation needed
- Easy settings with user friendly interfaces on WISE Studio utility
- ISO 10816-1 compliant
- Support wide temperature -20 ~ 80 °C (Battery-powered)
- IP66 enclosure design

INTRODUCTION

WISE-2410 is a LoRaWAN wireless condition monitoring sensor integrated with an ARM Cortex-M4 processor, LoRa transceiver, 3-axis accelerometer and temperature sensor. It balances the wireless bandwidth between WISE-2410 and the gateway, so it also mitigates the data transmission fail rates between edge-devices and gateways.

Star Topology

WISE-2410 is a LoRaWAN uses a star network topology and features a gateway data relay function between sensors and the application server. The communication between the sensors and gateway goes over the wireless channel, utilizing the LoRa physical layer, whilst the connection between the gateways and the central server are handled over a backbone IP-based network or over Modbus protocol to the application server.

Computing on Board

With an ARM Cortex-M4 Processor, WISE-2410 enables users to implement more features inside. WISE-2410 is able to calculate more complex eigenvalues itself, such as VRMS, ARMS, Peak, Displacement, Kurtosis, Crest factor, Skewness and Standard Deviation values. With its edge computing capability, WISE-2410 can balance the loading between WISE-2410, gateway, and cloud service.

Plug & Play with 2-year Battery life cycle

WISE-2410 includes two 3.6V AA battery holders. Along with LPWAN technology verified by Advantech, the battery life on WISE-2410 can be up to 2 years with once per hour data update interval time. With IP66 protection design, WISE-2410 is ideal for Low-Power Wide-Area Network (LPWAN) applications, such as pumps, HVAC system, motors, facility monitoring and more. WISE-2410 connects to Advantech's WISE Studio Utility for more user friendly and efficient installation.

Common Specification

Wireless Communication

Frequency Band	EU 863-870 (MHz) / RU 864-870 (MHz) US 902-928 (MHz) / AU 915-928 (MHz) AS 919-924 (MHz) / TH 920-925 (MHz) JP 920-928 (MHz) TW 920.3-923.4 (MHz)
Spreading Factor	7~12
Transmit Power	Up to 20dBm
Topology	Star (LoRa/LoRaWAN)
Sensitivity	-148dB
Data Rate	50 kbps at FSK mode EU 21.9 kbps at SF7 mode US 5.47 kbps at SF7 mode for JP/TW

General

Power Input	3.6V AA Battery *2pcs (Not included)
Battery Life	2 years (once per hour data update interval time)
LED Indicator	Power, Tx
Configuration Interface	Micro-B USB
IP Class	IP66
Mounting	Stud mount, Mounting pad and Adhesives
Dimension (H x D)	84.7 x 48.3 mm
Certification	CE (RED), FCC, NCC, TELEC, VCCI, BSMI, RCM, ANATEL

Environment

Operating Temperature	-20°C ~ 80°C (Battery powered)
Operating Humidity	10% ~ 95% RH
Storage Temperature	-25°C ~ 90°C
Storage Humidity	5% ~ 95% RH

3-AXIS ACCELEROMETER SENSOR

Axis	X-Y-Z
Frequency Range	10~1000Hz
Amplitude Range	±16g
Statistical Time-Domain	Velocity RMS, Acceleration (RMS & peak), Displacement, Kurtosis, Crest factor, Skewness, Standard deviation
Output Data Rate	6600Hz
Resolution	10 bit (all g range)
Accuracy (FC =100Hz)	Under 5%
Noise (MAX. TA = 25°C. 0g)	±40mg
Nonlinearity	±0.5 %
Cross-Axis Sensitivity	±1 %
Sensitivity Change Due to Temperature	±0.02 %/°C

TEMPERATURE SENSOR

Measurement Range	-20°C ~ 120°C
Accuracy (TA = 27°C, Directly contact with heat source (Metal Base of WISE-2410)	-2°C with 85°C -5°C with 120°C

ORDERING INFORMATION

Smart Condition Monitoring Sensor

WISE-2410-NB	Wireless Smart Condition Monitoring Sensor - US 902-928 (MHz)
--------------	---

Firmware Image (Optional)

9662410AJ00	WISE-2410-JA Patch
9662410AT00	WISE-2410-TA AS923 Patch
9662410AK00	WISE-2410-KA Patch
9662410AZ00	WISE-2410-ZA AU915 Patch

WISE-2410-EB	Wireless Smart Condition Monitoring Sensor - EU 863-870 (MHz)
--------------	---

Firmware Image (Optional)

96632410R00	WISE-2410-RA Patch
-------------	--------------------

LoRaWAN Gateway

WISE-6610-N100-A	LoRaWAN gateway supports up to 100 nodes with 915 MHz
WISE-6610-E100-A	LoRaWAN gateway supports up to 100 nodes with 868 MHz
WISE-6610-A100-A	LoRaWAN gateway supports up to 100 nodes with 923 MHz

Accessories

1760002647-01	Bat.Cylindrical 3.6V/2500mAh AA Li/SOCI2
25F7000004N000	Magnet base D30XH9mm for WISE-2410 installation
WISE-2410-MTB01	Metal base for WISE-2410 installation

