

Ambient Light Sensor



The Ambient Light Sensor utilizes LoRaWAN connectivity to provide measurements of ambient light intensity which matches the human eye's response to light under a variety of lighting conditions.

FEATURES

- EU, US frequency support
- LoRaWAN1.0.3
- Optical sensor LTR-F216A
- 16to20 bits measurement resolution
- Wide dynamic range (0.01 to 39K lux) with linear response
- 0 to 50°C operation temperature range

Specification

Frequency	868MHz & 915MHz
RF TX power	US:+19dBm EU:+17dBm
Antenna Gain	-2dBi Peak, -5dBi Avg
RF Sensitivity	-135dBm
Battery Type	3.6V ½ AA Li-SOCl ₂ , 1200mAh
Battery Lifetime*	Up to 16 months
Average Current	135mA maximum/ 100uA minimum
Protocol	LoRaWAN1.0.3
Operation Temperature	0 to 50°C
Environmental Rating	IP40 equivalent
Dimensions	50mm x 20mm x 50mm
Weight	30g without battery 40g with battery
Sensor	Wide dynamic range (0.01 to 39K lux)
Type Approval	FCC/IC/CE

SKU Detail

SKU	Country	Channels	Frequency Band (MHz)
TBAM100-868	Europe	8	EU868 (862~870)
TBAM100-915	USA	16	US915 (902~928)

* Samples are also available for IN865,AS923,AU915,KR920.